

# **FULL FIELD 3-D GEOACOUSTIC INVERSION**

Alexandra Tolstoy  
4224 Waialae Ave, Suite 5-260, Honolulu HI 96816  
Voice: 808-735-8070, Fax: 808-735-8086  
atolstoy@ipdinc.com  
N00014-95-C-0084  
Shallow water acoustics

## **LONG-TERM GOALS**

The full field 3-D geoacoustic inversion method is eventually intended for real-time estimation of range, depth, and azimuthally varying shallow water environmental properties by non-invasive, acoustic, remote sensing means via simple broadband sources such as SUS. The estimated environmental properties would then be available as input parameters to fleet acoustic propagation models used for the detection of targets, e.g., subs or mines.

## **OBJECTIVES**

The objective of this approach is to estimate those environmental parameters to which acoustic fields are sensitive. Such environmental parameters include: number of sediment layers, sediment thicknesses, densities, and sound-speed profiles. The intention is to replace present requirements for extensive environmental sampling (which can be extremely time-consuming and expensive) with intense computational processing of array data (with limitations determined primarily by the nature of the array configuration and the computer system available for data processing).

## **APPROACH**

The full field approach involves using measured array data for a broadband source with good signal-to-noise levels at frequencies from 50 to 500Hz. The measured fields are compared to modeled fields where the model environmental inputs are varied in a systematic way so as to converge to a set of values which optimize the correlation between data and model. The principle assumed is that high correlations will indicate input values 'closer' to the 'true' environmental values, i.e., those which would be measured given sufficient resources. The 'true' values would result in accurate predictions for acoustic fields over the broadband of frequencies and over the selection of target ranges of interest. Unlike the focalization approach our method hopes to estimate the 'true' geoacoustic parameters.

## **WORK COMPLETED**

Work completed includes the organization and chairing (shared with R.Chapman) of a workshop devoted to the comparison of available geoacoustic inversion techniques

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>30 SEP 1997</b>		2. REPORT TYPE		3. DATES COVERED <b>00-00-1997 to 00-00-1997</b>	
4. TITLE AND SUBTITLE <b>Full Field 3-D Geoacoustic Inversion</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>IPD Inc,4224 Waialae Ave, Suite 5-260,Honolulu,HI,96816</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>3</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

applied to benchmark data sets. This workshop was well attended with over 20 presentations over 3 days. The results are being compiled into a Special Issue of the Journal of Computational Acoustics to be published in Spring/Summer of 1998.

## **RESULTS**

Over the past 12 months we have emphasized the analysis of simulated, benchmark data for geoacoustic inversion processing. This has been highly important for the understanding of inversion limitations and potential accuracies and has resulted in major improvements in the tomographic inversion method under study. We are also finding successful ways to search the large solution spaces and to eliminate non-uniqueness difficulties in solution estimation. We have also made significant progress in understanding what bottom and geometric properties affect the relevant acoustic fields and how important are those properties; what are the optimal frequencies for processing to estimate those properties; and what are the optimal array and source configurations?

Thus, we have continued to advance the capabilities of the tomographic, high resolution MFP based inversion method (RIGS) which has been under development for this project. The RIGS method (Refined Iterative Grid Search) was applied to the workshop data with excellent results. Conclusions to date include: broadband processing is critical, the propagation model used is critical (KRAKEN was found to have significant difficulties but incorporating ORCA can overcome those), physical insight to efficiently organize parameter searches can be very helpful, and some parameters are easily estimated with high accuracy (such as source coordinates, water depth, sediment density and attenuation).

## **IMPACT**

If this technique proves to be successful, it could influence array technology and the selection of propagation models used by the fleet for target detection and localization. It could also affect fleet strategy for the calibration of a region's environmental parameters with resultant target searches prior to subsequent commitment of fleet resources. The estimation of true geoacoustic properties will be extremely important for the detection and localization of targets such as subs as well as of buried targets such as mines.

## **TRANSITIONS**

The Workshop97 and RIGS results are influencing a host of methods for geoacoustic inversion (see next section).

## **RELATED PROJECTS**

Many inverse techniques are currently being pursued to determine bottom properties, and the newest involve the use of MFP for a signal measured along an array of receivers. The MFP techniques often involve simple least squares fits of model predictions to data which are subsequently combined with computationally intense, random number based methods

such as simulated annealing (Chapman, Dosso, et al.). The full field 3-D geoacoustic inversion approach being developed in this work is NOT a least squares fit NOR is it random-number based. It is based on the high resolution non-linear minimum-variance (MV) processor plus a global, directed search through parameter space.

Other investigations in the area of geoacoustic inversions are being conducted by the Canadians (Chapman et al.; Heard et al., Zala and Ozard), Europeans (Hamson and Ainslie of Great Britain; Jesus of Portugal; Siderius and Gerstoft of SACLANT Centre; Simons and Snellen of The Netherlands; Stephan et al. of France; Taroudakis and Markaki of Greece; Westerlin of Sweden), and Asians (Ratilal et al. of Singapore; Zhang et al. of China).

## REFERENCES

Dosso, S.E., M.L. Yeremy, J.M. Ozard, and N.R. Chapman, Estimation of ocean-bottom properties by matched field inversion of acoustic field data,"IEEE J. Oceanic Eng., 232-239 (1993).

Gerstoft, P., Inversion of acoustic data using a combination of genetic algorithms and the Gauss-Newton approach,"J. Acoust. Soc. Am., 2181-2190 (1995).

Tolstoy, A., Matched Field Processing in Underwater Acoustics, World Scientific Publishing, 1993.

Tolstoy, A., Using matched field processing to estimate shallow water bottom properties from shot data taken in the Mediterranean Sea,"in IEEE J. Oceanic Eng., Vol 21, No. 4, pgs. 471-479, Oct. 1996.